

change for the better



*PNEUMATIC HEAT IMPLUSE
WELDING MACHINE*

unifot SA

Parameter

Model	FMQP-1200/2	FMQP-2500/2	FMQP-3000/2	FMQP-4000/2	FMQP-5000/2
Power	2.5KW	5KW	6KW	8KW	10KW
Voltage	220V,50Hz	220V,50Hz	1 or 3 Phase	3 Phase	3 Phase
Air Source	0.6MPa	0.6MPa	0.6MPa	0.6MPa	0.6MPa
Sealing Length	1200mm	2500mm	3000mm	4000mm	5000mm
Sealing Width	25mm	25mm	25mm	25mm	25mm
Size	1390×1120×1250 mm	2700×1120×1250 mm	3200×1120×1250 mm	4190×1120×1250 mm	5190×1120×1250 mm
Weight	360KG	620KG	700KG	860KG	1020KGa

Welding Type



Overlap weld



**Overlap weld with
tape on one side**



**Butt weld with tape
on double sides**



Hem



Hem with pocket



Kedar weld

Optional Parts

Extension table

4 pieces in 1 set. Intend to hold the banner which ensures that the two end of the welding is smooth and can slide to the next weld.

New measurement system

A block piece help placing the banner

Tape roller support with self brake

Suitable for overlap weld with tape on one side.

Kedar holder

Hold the kedar to ensure the precise weld with no deflection.

Laser light

Mark on the welding bar to show the position where the banner should be.

Piston holder

A holding bar with piston pressure which hold the position of the banner incase that it moves before welding.



Control Panel

9 memory program can meet the need for different material or thickness welding. PCB digital control with display is very easy to operate.

Standard Features

Digital control
Automatic heat/sealing settings
9 memory programs
Uniform pressure & sealing
Precise fabric welding
Efficient & easy operation
Maximum comfortable design
Automatic stop safety features
Thermo impulse welding technology
Safety features OE approved